

TC-610

Professional Two-way Radio

Harsh, noisy and dusty working conditions in mega-project and construction sites may lower your efficiency and productivity by smudging the radio or shadowing the talk. HYT TC-610 portable radio is the option customized for users in these industries, as its superior dust & water protection performance helps to seal out dust and water, and thus prolong radio life.

- Dust/Water Protection Class IP66
- Powerful Audio and Wide Communication Range
- Reliable Mechanical Design
- Innovative Industrial Design





TC-610

Professional Two-way Radio

Super Features

Dust/Water Protection Class IP66

In harsh, noisy and dusty working conditions such as construction sites and engineering sites, your radio is apt to be smudged. The TC-610 portable radios are IP66-rated and have excellent dust/water protection performance. The IP66 protection allows you to wash off mud and dust on your radio. A water jet (40mm \varnothing) from a nozzle, which is projected from any direction against your radio for up to one minute, must not have any harmful effect. Your radio could be dried to operate normally after you wash it.

Powerful Audio and Wide Communication Range

Superior audio quality is the premise for your team to work efficiently in noise environments. A powerful speaker with size of 45mm \varnothing (36mm \varnothing speaker for common radios) ensures clear and crisp sound, even in noisy environments. You can also use high transmit power for wide communication coverage.

Reliable Mechanical Design

Battery latch is apt to become loose after long time use, and even occasionally causes your radio to shut off automatically. All these will affect your working efficiency. HYT proprietary battery latch mechanism is applied to TC-610 radios. It delivers secure connection between battery and radio, no matter how long the radio has been in use.

Innovative Industrial Design

The TC-610 abandons conventional black body, and employs fashionable yellow rubber housing, making the radio more comfortable to handle.

• IP66 water protection ensures the radio to be protected against a water jet for one minute. The diameter of the water jet is 40 mm.

Main Features and Functions

High/Low Power Switchable

By simple pressing one button, users can switch to low power when communicating within limited range coverage or switch to high power when further distance is required. High transmit power optimizes range coverage while low transmit power conserves battery consumption, all at the user's control.

Programmable 12.5kHz / 25kHz Channel Spacing

The feature enables flexibility and easy migration of channel spacing requirements when the need arises, with no need to buy new radios.

Monitor

Allows users to monitor the activity on the current channel. The feature is especially helpful for receiving a weak signal.

Battery Save

The Battery Save feature is automatically activated once no activity on the channel and no operation performed, for extended operation time.

Low Battery Alert

Alert users to recharge the battery should the battery level run low.

Busy Channel Lockout

A channel already in use is not available to other users.

Time-out Timer

The feature allows for more efficient use of channels by limiting the amount of time of each transmission.

PC Programmable

You are able to customize the features of each radio for each user.

Wired Clone

Easily copy the features of one radio to another.

CTCSS/CDCSS

Set up workgroups/users with unique CDCSS/CTCSS to prevent unwanted conversations on the same frequency. ▶

Selectable Squelch Level (0-9)

Helps minimize interference from undesired weak signals and helps weak signals be heard.

Channel Scan

The channel scan feature enables the radio to continuously scan each channel in the scan list for activity. Simply press a side function button to activate scanning. When activity is detected on a channel the scan process will stop and you will hear the transmission.

Voice Operated Transmit (VOX)

Enjoy the convenience of hands-free operation when used with optional accessories.

Recommended Applications

- Construction sites
- Hotel
- Manufacturing
- Property management
- Ports
- Warehousing

Accessories

Standard Accessories

U/V Antenna MCU Charger CH10A03 Belt Clip BC12 Li-ion Battery (1200mAh) BL1204
Switching Power Adapter (different P/N for different countries and areas) Strap RO03

Optional Accessories



Li-ion Battery (2000mAh)
BL2001



MCU Rapid-rate Multi-unit
Charger for Li-ion/Ni-MH
Batteries MCA02



Lightweight Single-muff
Headset with in-line
PTT & VOX
ECM12



Earpiece with on-MIC
PTT & VOX & Transparent
Acoustic Tube EAM12
2-Wire Surveillance Earpiece
with VOX & Transparent
Acoustic Tube (black)
EAM13
3-Wire Surveillance Earpiece
with Transparent Acoustic
Tube (black/beige)
EAM16 / EAM15




Water Resistant Remote Speaker
Microphone (IP56) SM13M1




Noise-cancelling Remote
Speaker Microphone
(350-390MHz) SM13M2



Remote Speaker
Microphone SM08M3



Receive-only Earpiece with
Transparent Acoustic Tube
(for use with remote speaker
microphone)
ESS08



Receive-only Earbud
(for use with remote speaker
microphone)
ESS07



2-wire Earpiece with
Wireless Receiver and
Neck Loop (Beige) EWM03




Behind-the-head,
Noise-cancelling
Headset ECM14




Heavy Weight
Noise-cancelling
Headset ECM13




Light Weight, Throat-
vibrating Earpiece ELM01



Ear Canal Bone Induction
Earpiece EBM01



D-earset with Boom
Microphone & in-line
PTT & VOX EHM16
D-earset with in-line
PTT & Microphone & VOX
EHM15



Universal Chest Pack
(Nylon)(Black) LCBN13
Leather Carrying Case
(non-swivel)
LCBN56



Earbud with in-line
PTT & VOX ESM11
Earbud with on-MIC
PTT & VOX ESM12



Applicable MIL-STD-810C/D/E/F

Applicable MIL-STD	810C		810D		810E		810F	
	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	1,2	500.3	1,2	500.4	1
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2	501.4	1,2
Low Temperature	502.1	1	502.2	1,2	502.3	1,2	502.4	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1	503.4	1
Solar Radiation	505.1	1	505.2	1	505.3	1	505.4	1,2
Rain	506.1	2	506.2	2	506.3	1,2	506.4	1,2
Humidity	507.1	2	507.2	2,3	507.3	2,3	507.4	1
Salt Fog	509.1	1	509.2	1	509.3	1	509.4	1
Dust	510.1	1	510.2	1	510.3	1	510.4	1
Vibration	514.2	8,10	514.3	1	514.4	1	514.5	1
Shock	516.2	1,2,5	516.3	1,4	516.4	1,4	516.5	1,4

General

Frequency Range(MHz)	VHF: 136-174 UHF: 400-420 440-470 420-450 450-470 420-470 470-490
Channel Capacity	16
Channel Spacing(KHz)	25 /12.5
Operating Voltage(V)	7.4
Battery	1200mAh (Li-ion)
Battery Life (5-5-90 Duty Cycle)	More than 9 hours
1200mAh Li-Ion battery	More than 9 hours
1300mAh Ni-MH battery	More than 14 hours
2000mAh Li-Ion battery	
Frequency Stability(ppm)	± 2.5
Operating Temperature(°C)	-20~+55
Antenna Impedance(Ω)	50
Dimensions (H×W×D)(with battery, without antenna)(mm)	119×55×33
Weight (with antenna & battery)(g)	270

Transmitter

RF Power Output	5W/2W(VHF) 5W/2W(UHF)
Modulation	F3E
Spurious and Harmonics	-36dBm<1GHz -30dBm>1GHz
FM Noise	40/35dB
Audio Distortion	≤5 %

All Specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development.

Receiver

Sensitivity	0.25/0.28 μ V
Selectivity	70/60dB
Intermodulation	≥65dB
Spurious Response Rejection	≥70dB
S/N	45/40dB
Rated Audio Power Output	800mW
Rated Audio Distortion	≤5%



Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

Http: //www.hytera.com

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All Rights Reserved.

Your Local Dealer